

Unmanaged Ethernet Switch

NSW1010-8GT-IN

Overview

The NSW1010 series unmanaged Ethernet switch is a plug-and-play device with no configuration required. The fanless silent design completely eliminates the loud noise caused by other small switches used in the office. The small size and exquisite appearance save the space effectively. It can be widely used in industries such as network video management, hotels, campuses, small and medium-sized enterprises network, etc.



Features

- Supports IEEE802.3 and IEEE802.3u standards.
- Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
- Supports auto MDI/MDIX.
- Supports IEEE802.3 flow control for full-duplex mode and backpressure for half-duplex mode.

Specifications

Model	NSW1010-8GT-IN	
Hardware Specification		
Ports Type	8 x 10/100/1000Mbps port (RJ45)	
Network Media	10Base-T: Cat3, 4, 5 or higher UTP/STP (≤100m)	
	100Base-TX: Cat5 or higher UTP/STP (≤100m)	
	1000Base-TX: Cat5e or higher UTP/STP (≤100m)	
Switching capacity	16 Gbps	

1

unv		DATASHEET	
Forwarding performance	11.9Mpps		
MAC	2K		
Jumbo Frame	15K		
Transfer Mode	Store-and-forward		
Dimensions (W×D×H)	Product: 145*60*21.5mm		
	Packaging: 146*88*50mm		
Carton Information	Carton dimensions: 530*475*315mm Carton quantity: 100PCS		
	Carton weight: 17.6kg		
Weight	Product: 0.111kg Packaging: 0.166kg		
Power Supply	Adapter input voltage: AC 100V to 240V Switch input voltage: 5V, 1A		
Mount Method	Desktop mount, wall mount		
Cooling Fans	0		
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)		
Operating humidity	10%~90% (non-condensing)		
Storage Temperature	-20°C to 70°C		
Storage Humidity	5% to 90% RH, noncondensing		
Indicator	POWER Steady on: AC input is normal, POWER Off: No AC input, LINK/ACT Off: No link, LINK/ACT Flashing: Transmitting data, LINK/ACT Steady on: Linked		

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China (Zhejiang) Pilot Free Trade Zone, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2024-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.