

Ossia VMS Hardware

PROVISION-ISR dedicated VMS hardware is planned, designed, and built by Provision-ISR with the sole purpose of running OSSIAVMS: a top-quality Central Management System allowing the user to view and manage multiple devices from remote.



OC-MSCL-S(DT)-V2

Ossia VMS embedded Management Server / Client supports up to 256 Channels

OC-MSCL-S(DT)-V2 server/workstation is mainly developed for small to medium-sized security systems. Provision-ISR delivers a winning solution to the field of security with designated hardware that runs embedded Ossia VMS. This design makes the system far more stable, cost-worthy, and easy to use. As a result, the device is fully dedicated to its task – CCTV management and operation.



MAIN FEATURES

- OC-MSCL-S(DT)-V2
- Max Channels: 256
- Included License: 256
- 3rd Party Channels: 32 (Max)
- Max Devices: 64
- Max 3rd Party Devices: 32 (Max)
- Video Output: 1 x HDMI (4K), 1 x VGA (1080P)
- Storage Server Support: No
- Transfer Server Support: Integral Only
- Video Decoder (TV Wall) Support: Yes (Up to 64 HDMI Outputs)
- Playback: Up to 32Ch (Restrictions Applies)
- Bandwidth: 128Mbps
- Online Users: 36 (4 By PC client, 32 by mobile App)
- Network: 1 x 1Gbps
- Local Recording: None
- Installation: Desktop
- Size: 154mm x 120mm x 30mm
- Weight: ~0.47Kg
- Power: DC 12V/3A



SPECIFICATIONS

MODULES	
Live View	Live view of cameras including groups, alarm views and E-Map monitoring, Two-Way Audio and Audio Broadcasting
Playback & Backup	Multi Channel playback based on Time Search, Events, Time Slice and Tags
E-Map	Based on Static JPEG image / Live Google Maps® Location
TV Wall Management	Set TV Wall and Encoders view (Including Live View, Playback and Alarm Popup Windows)
Resource Management	Manage your Cameras, recording devices and optional Ossia VMS hardware
People Management	Create and manage different groups of people and synchronize with Face Recognition devices
Account and Permission	Up to 64 Accounts and Permission groups defined by the user
Alarm Center	View and configure alarm events and system responses + SOP configuration
LPR Monitoring	Configure your LPR monitoring points, vehicles and access barriers
Face Recognition	Supports All Provision-ISR's Face Recognition Devices + Multiple Device Database Sync.
Face Greeting	Utilize an external screen to display a greeting message welcoming recognized faces
Face Attendance	Use the Ossia VMS as an attendance system based on face recognition
People Counting	Configure counting tasks for multiple supporting DDA cameras
Operation and Maintenance	See logs, and overall system status
Temperature Units	Set and monitor EC-001 devices including alarm events
Local Configuration	Configure all local settings regarding the Ossia VMS server / client configuration

HARDWARE	
CPU	Intel Pentium 4405U
NDAA Compliant	Yes
GPU	Integrated Graphics, Intel HD Graphics 510
RAM	8GB DDR RAM (Non-Expandable)
Network Card	RJ45 10M/100M/1000M self-adaptive Ethernet port
HDD	Built-in 128GB SSD

PCI Expansion	None
SATA	None

INTERFACE

Display	HDMI + VGA Independent Display
LAN	1 x 1Gbps
Keyboard / Mouse	By USB only
USB	6 Total [2 x USB3.0 + 2 x USB2.0 (Rear Panel) + 2 x USB3.0 (Front Panel)]

PERFORMANCE

Display	HDMI + VGA Independent Display
Max Channels	256
Included License	256
3rd Party Channels	32 (Max)
Max Devices	64
3rd Party Devices	32 (Max)
Device Group Support	Yes
Local Decoding Capability	Single monitor 1080P: Up to 32 CH @ CIF – Dual monitor 1080P: Up to 17 CH @ CIF per monitor – Single monitor 4K: Up to 33 CH @ CIF – Dual monitor 4K+1080P Up to 17 CH @ CIF per monitor
Incoming Bandwidth	128Mbps
Outgoing Bandwidth	128Mbps (Live + Transfer)
Max Streaming Capability	Depends on Bandwidth
Registered Users	Up to 64
Max Online Users	36 (4 By PC client, 32 by mobile App)
Fish-Eye Support	No Dewarping (v2.1.2) Full Dewarping (v2.1.3)
PTZ Support	Movement / Presets Management

Local Playback	Up to 32Ch
Remote Playback	Up to 100Ch (Recording device restrictions apply)

PLATFORM CONNECTIVITY

Video Decoder	Yes (Up to 64 HDMI Outputs)
Storage Server	No
Video Transfer Server	Integral Only
Joystick	Yes
Client Support	Yes (4 By PC Client, 32 by Mobile App. Outgoing Bandwidth restriction apply)
Web-Client Support	No

GENERAL

Management	Local Configuration, Remote management by PC Client
Installation	Desktop
Operation Temperature	Working: -5°C ~ 45°C, Standby: -20°C ~ 70°C
Noise	N/A
Protection Rate	None (Indoor Installation)
Net Weight	~0.47Kg
Dimensions	154mm x 120mm x 30mm
Power	DC 12V/3A

3rd Party Cyber Protection

General	Quantum IoT Nano agent by Check Point™
Protection Methods	Shell injection protection, File Monitor, Import-Table Protection, Dynamic-Memory Protection