


# Control Module M201E



- **ADM loop technology with System Sensor/200AP protocol**
- **One monitored output or dry relay contact**
- **Output line monitored for wire breakage and short circuit**
- **Setting of module address via decadic rotary switches**
- **Mounting in module box or by means of mounting base**



## Description

The addressable Control Module M201E serves for the actuation of an external device via the bi-directional communication on the loop with System Sensor/200AP protocol. The control module provides two modes for actuation of the external device: In the monitored mode an external power supply can be switched to the line-monitored output. In the unmonitored mode a dry change-over relay contact can actuate the external device.

The way of actuation and the monitoring mode can be selected by means of DIL-switches.

A status LED indicates the condition of the control module. Separate terminals enable the operation of the module with or without the integrated dual-isolator.

Accessories for mounting on a wall, on a plate or on a DIN rail are available.

## Specifications

Operating voltage	Supply through loop voltage
Current consumption	approx. 510µA (quiescent)
Contact rating	2A/30VDC or 0.5A/30VAC
Ambient temperature	-20°C to +60°C
Dimensions L x W x H	93 x 94 x 23 (mm)
Colour	cream
Weight	110g
Approvals	VdS G202141 0786-CPD-20341
Order number	249103
Order name	Control Module 1xSurv.Out/200 M201E



0786-CPD-20341

*Building Safety. Building Security.*



### Surface Mounting Box


Dimensions L x W x H	132 x 137 x 48 (mm)
Order number	249108
Order name	Surface Mounting Box M200SMB

### Base for Mounting Plate

Order number	249109
Order name	Base for Mounting Plate/M200 M200E-PMB

### Base for Carrier Rail

Order number	249110
Order name	Base for Carrier Rail/M200 M200E-DIN



*Building Safety. Building Security.*

