


40M IR FIXED LENS BULLET CAMERA

I4-340IPE-36



- | | | | |
|-------------------------------------|--------------------------------------|---------------------|-----------------------|
| 1/2.8" CMOS Sensor | ONVIF | Audio Input | Micro SD Card Support |
| 2 Mega-Pixel | True WDR | 3.6mm Fixed Lens | Technician Port |
| True Day & Night (IR Cut Removable) | 3D Noise Reduction | 40m IR Illumination | |
| H.265 (HEVC) Compression | Motion Detection and Privacy Masking | PoE Support | |
| 0 Lux (IR On) Min. Illumination | AI Analytics (DDA + Face Detection) | IP 67 Protection | |

Specifications

Camera	Video	Model	I4-340IPE-36
		Image Sensor	1/3" CMOS (16:9)
		Effective Pixels	2592X1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS In Normal Mode. 1-50/60FPS in HFR Mode***
		Day & Night	ICR
	Audio	Min. Illumination	Day: 0.1lux / Night: 0.005lux (@F1.6, AGC On) 0lux with IR on
		Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB), BLC, HLC, ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
Compression	Analytics	Object Detection (Sterile Area, Line Crossing, Object Counting), Face Detection (10 Faces per frame), Camera Tampering	
	Video Compression	H.265S/H.264S*, H.265+/H.264+/H.265/H.264/MJPEG**	
	Resolution	4MP / 2K / 3MP / 2MP / 1MP / D1 / QVGA / CIF	
	Multi-Stream	Master Stream: 4MP(2592x1520) / 2K (2560x1440) / 3MP / 2MP / 1MP Sub-Stream: 1MP/QVGA/D1/CIF Third Stream: QVGA/D1/CIF (1~30fps)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 64Kbps ~ 8Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	40m (2 High Power IR LED)
	Lens (Field of View)	3.6mm Fixed Lens (80.6°)
	Iris	Fixed Iris
	Lens Mount	M12 Mount
	Protection Rate	Water Proof: IP67
	Bracket	3-Axis Bracket
Connectivity	Dimensions	220.8x79.4x81.2mm
	Weight(gross)	~650g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Audio Connectivity	Audio Input
	SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 128Gb)
Network	Hard Reset Button	Yes
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 10 users with multi-stream real time transmission
Others	Network Protocol	IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS, P2P
	ONVIF	Yes
	Ethernet	100Mbps
PoE		Yes
Power Supply		DC12V/~780mA / PoE/~7.4W
Work Environment		-30°C~60°C, 10%~90% Humidity

*Main Stream Only, **Sub-Streams Only, ***1080P, No True-WDR

