## 8CH Face Recognition NVR



## NVR8-8200FA





M	DDEL		NVR8-8200FA
Video		Input	8CH Over Network
		Output	HDMI (4K@60Hz, 4K@30Hz, 1080P), VGA (1080P, 1280x1024, 1024x768)
		Decoding Format	H.265 (HEVC) / H.264
		Decoding Capabilities	1Ch - 8MP ; 4Ch - 2x8MP + 2x5MP ; 9Ch - 1MP
		Analytics Channels	8Ch (Requires supporting IPC)
		Supported Analytics	Face Recognition, Smart Search, Camera Tampering, Line Crossing, Sterile Area, Object Monitoring
Analytics			People Counting, People Intrusion, Crowd Gathering
		Face Recognition Rate	240 Faces per minute (All Channels) / 5 Faces per second (Single Channel)
Audio		Input	1CH + Depends on Camera Inputs
		Output	1CH + Depends on Camera Outputs
		Two Way Audio	Yes
		Incoming	80Mbps
ва	ndwidth	Outgoing	80Mbps
ġ	Record/ Main Stream	Real-Time Recording	8CH 8MP Real-Time
App.		8MP	480FPS (NTSC)/400FPS (PAL)
Remote		5MP and lower	480FPS (NTSC)/400FPS (PAL)
Ĕ		Master Streams over Network	Up to 12CH@Recording Resolution
Re	Sub	Resolution	Depends on IPC
Record /	Stream	Sub-Streams over Network	Up to Outgoing Bandwidth Capacity
Š	General	User Access	10 Users Online with Professional Autorithy Management
š		Recording Modes	Schedule, Manual, Motion, Sensor, Analytics
_		Applications	Provision Cam2 for iOS/Android, IE for Windows 7/8/10, Safari for Mac OS, CMS for Windows/MAC
		Playback (Local / Remote)	8Ch / 8Ch
Playback		Search Mode	Smart Search, Face Recognition, Time-Slice, Time, Event, POS, File Management
Backup		USB	1 USB 2.0 Port + 1 USB 3.0 Port
		Backup Format	AVI/DAT
Alarm		Input	8 + Depends on Camera
		Output	4 + Depends on Camera
Storage		HDD	1 SATA (8TB Max)
		E-SATA	No
		RAID	Not Supported
PTZ		Connection	Via Network
		Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
		RS-485	Yes (C06 Keyboard Connection)
Network		Ethernet	1000 Mbps (RJ-45)
		Protocols	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP, FTP, HTTPS, 802.1X, SNMP, NAT
		ONVIF	Yes (For IP Channels)
PoE		Ports	No
		Interface	No
		Standard	No
		Total Power	No
		Max. Power Output (Per Ch.)	No
		Power Supply	DC12V/2A
Others		Power Consumption (No HDD)	10W
		Dimention	W375xD275xH50mm
		Operation Temperature	0°C ~50°C