

## DS-6101HFI-IP-SD Digital Video Server



### Key Features

- High performance DSP hardware compression
- H.264 video compression
- Dual streams
- Support variable bit rate and frame rate
- SD card for local storage up to 32GB
- Embedded Linux OS
- Conform to Onvif, PISA, CGI

### Specifications

		DS-6101HFI-IP-SD
Video/Audio Input	Video compression	H.264
	Video input	1-ch
	Video input interface	BNC (1.0 Vp-p, 75 Ω)
	Audio compression	OggVorbis, 16 Kbps
	Audio input	1-ch
	Audio input interface	BNC(2 Vp-p, 1 kΩ)
	Voice talk input	1, RCA 2.0 Vp-p, 1 kΩ
Video/Audio Output	Encode/Decode resolution	4CIF / DCIF / 2CIF / CIF / QCIF
	Frame rate	Up to 4CIF @ 30 fps
	Stream type	Video / Video & Audio
	Support dual stream	Yes
	Video bit rate	32 Kbps ~ 2 Mbps, or user-defined (Max. 8Mbps)
	Audio output	1 Channel RCA (Linear Electrical Level, 600 Ω)
External interface	Network interface	1 RJ45 10M/100M adaptive Ethernet interface
	RS-232 Port	1 RJ45 RS-232 Port
	RJ-485 port	1 (T+, T-)
	Alarm input	1-ch
	Alarm output	1-ch
General	Power supply	12 V DC
	Consumption	≤ 3 W
	Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
	Working humidity	10% ~ 90%
	Dimension (WxHxD)	70 x 45 x 120 mm (2.76" x 1.77" x 4.73")
Weight (without HDD)	≤ 500 g (1.10 lbs)	