

# CD9381-HNVF2


Corner Dome Network Camera

---

5MP 30fps • 10M IR • 940nm IR • IK10+ • IP67 • Anti-Ligature • Anti-Grip

- 30 fps @ 2560x1920
- H.265 Compression Technology with Smart Stream III
- SNV, WDR Pro and Smart IR
- Signed Firmware and Secure Boot
- Smart Motion Detection to Reduce False Alarms
- Trend Micro IoT Security for Cyber Protection
- Weather-proof IP6K9K/IP67-rated and Vandal-proof IK10+ rated Housing
- Built-in Invisible 940nm IR Illuminators up to 10 Meters
- Anti-Ligature Design, Corner Dome Correctional Facility Camera
- Built-in Microphone





# Technical Specifications

## System Information

Model	CD9381-HNVF2
CPU	Multimedia SoC (System-on-Chip)
Flash	8 GB
RAM	2 GB

## Camera Features

Image Sensor	1/2.7" Progressive CMOS
Max. Resolution	2560x1920 (5MP)
Lens Type	Fixed-focal
Focal Length	f = 2.4 mm
Aperture	F2.1
Iris Type	Fixed-iris
Field of View	124° (Horizontal) 92° (Vertical) 156° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut Filter	Yes
IR Illuminators	Built-in invisible IR illuminators, effective up to 10 meters with Smart IR, IR LED*2 (50IRE)
Minimum Illumination	0.07 lux @ F2.1(Color) <0.005 lux @ F2.1(B/W) 0 lux with IR illumination on
Tilt Range	0°
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card slot and recording to network-attached storage (NAS)
Built-in Installation Aids	Micro USB* *Requires Wi-Fi dongle and Micro B converter

## Video

Video Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 2560*1920 (WDR Pro on) 30 fps @ 2560*1440 (WDR Pro on) 60 fps @ 1920x1080 (WDR Pro off)
Maximum Streams	3 video streams (Up to 8 configurable profiles)
S/N Ratio	54 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and bit rate control, Smart Stream III
Image Settings	General settings: video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings; Illuminators: illuminators, anti-overexposure; Image settings: white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, EIS, scene mode (auto, deblur); Exposure: BLC, HLC, exposure control (exposure level, flickerless, exposure time, gain control), AE speed adjustment, WDR; Privacy mask; Pixel calculator; Scheduled profile settings

## Audio

Audio Capability	Two-way audio (Full duplex)
Audio Compression	G.711, G.726
Audio Interface	Built-in microphone External audio input External audio output
Effective Range	10 meters

## Network

Users	Live viewing for up to 10 clients
-------	-----------------------------------



Security	Access list, CSRF protection, digest authentication, HTTPS , IEEE 802.1x, Password protection, secure boot, signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event, quarantine event), user access log, user account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP/SFTP, HTTP/HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTPSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2, UDP, UPnP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) * It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>

### Solution Integration

Video Motion Detection	Five-window video motion detection, people detection, time filter
Smart VCA	Smart VCA (Default, license embedded) Intrusion detection, loitering detection, line crossing detection, unattended object detection, missing object detection, face detection, crowd detection, running detection
VADP Package	Deep Learning VCA (Smart Motion Detection, Smart VCA), Trend Micro IoT Security (3-year free trial)

### Alarm and Event

Event Trigger	Audio detection, camera tampering detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event), digital input, manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, shock detection, system boot, casing open detection
Event Action	Event notification via audio clip, camera link, digital output, email, HTTP, FTP/SFTP, NAS server, SD card File upload via email, HTTP, FTP/SFTP, NAS server, SD card

### General


Connectors	Default I/O RJ-45 cable connector for 10/100 Mbps PoE network connection Built-in Microphone Micro USB Audio output (Optional) Mic in (Optional) DC 12V power input (Optional) AC 24V power input (Optional) Digital input*1 (Optional) Digital output*1 (Optional) ((DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A))
LED Indicator	System power and status indicator
Power Input	AC 24V*, DC 12V*, IEEE 802.3af PoE Class 0 (Power Redundancy) *Requires I/O cable
Power Consumption	PoE: Max. 10.36/8.36 W (IR on/off) DC 12V: Max. 9.96/7.96 W (IR on/off) AC 24V: Max. 18/16 W (IR on/off)
Dimensions	226 x 221 x 112 mm
Weight	1.5 kg
Certifications	EMC: CE (EN 55032 Class A, EN 55035), UKCA (BS EN 55032: 2015 +A11: 2020, BS EN 55035: 2017 +A11: 2020), FCC (FCC Part 15 Subpart B Class A), RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A), ICES-003 Issue 7; Safety: UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471); Environment: IK10+ (IEC 60529), IP67 (IEC 60529), IP6K9K (ISO 20653); IA: BIS (IS 13252), BSMI (EMC: CNS 13438, Safety: CNS 14336-1)
Operating Temperature	Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working Temperature: -10°C ~ 55°C (14°F ~ 122°F) (IR off) -10°C ~ 40°C (14°F ~ 113°F) (IR on)
Humidity	98% RH (non-condensing)
Warranty	36 months

### System Requirements

Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above

### Included Accessories

Packing Contents	Quick installation guide, L-shaped wrench, screw pack, waterproof accessory pack, I/O cable, Ethernet cable with RJ45 female connector cable, Mounting bracket
------------------	--




---

**DORI (EN 62676-4 Standard)**

---

Detect (25PPM 8PPF)	47.9 m (157.20 ft)
Observe (63PPM 19PPF)	19.2m (62.80 ft)
Recognize (125PPM 38PPF)	9.5 m (31.30 ft)
Identify (250PPM 76PPF)	4.7 m (15.50 ft)

---



## Dimensions

