

ATS8520-2 User management tool - USB version

Product Overview

ATS8520 provides an easy, open look Windows® interface that simplifies the user management or control of Advisor Advanced or Advisor MASTER panels. Up to 20 panels can be managed separately. Each panel is configured one by one.

Up/download

A PC running ATS8520 can be connected to a control panel either remotely via the built-in PSTN dialer or ethernet/GPRS connection. Changes made to user configuration can be up/downloaded (all data) or synchronized (changes only)

Remote Command and Control

All Advisor Advanced control panels can run a Command & Control session with the ATS8520. It will provide a complete overview of the panel status including zone, area, communication path, etc. The ATS8520 can provide full control over the panel remotely based on the user options assigned

Real time event log

A real-time event log shows all events as they happen with a time and date stamped description of the event. History can be viewed as a constantly visible window in the Command & Control view.

Supported Languages

The ATS8520 supports following languages:

Danish, Norwegian, Finnish, Swedish, French, Turkish, Polish, Slowak, Czech, Dutch, English Irish, English UK, French, German, Italian, Portugal and Spanish

User management

User management includes operations related to create, modify or remove users, PIN codes of users, card assignment, access right assignment or schedules and holidays.



Details

- User management tool for smaller systems, managing up to 20 panels separately
- · Configure and modify users, assign cards and PIN codes
- Microsoft SQL database
- Command & Control with live history
- Real time event logging
- Manage schedules and holidays

ATS8520-2 User management tool - USB version

Technical specifications

General	
Product line	Advisor Advanced, ATS Master
Segmentation	Commercial
Software type	Management Software
Supported technology	Access Control, Intrusion
Supported hardware	Advisor Advanced, ATS Master
Max. number of PC with ATS8520 connected	1
Max. number of panels connected at the same time	20
Number of panels in database	20

Software details

Shipping weight

Software architecture	Standalone
License type	Free License

System requirements

Supported operating	Windows 10, Windows 7, Windows 8.x
system	
Database support	SQL
Minimum system requirements	Intel Dual Core i5 with 4GB RAM MEM: 256 MB (Minimum); 1GB (Recommended) HD: Up to 500 MB of available space may be required Display: 1024 x 768, 32-bit (Minimum), Note: for Windows 7, Home and Starter Editions are not supported.
Physical	
Net weight	80 g

110 g



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.