



VC3022

100 Volt Wall Volume Controller

► Features

- 20 Watt Volume controller
- Flexible (EURO) system
- 11 attenuation steps of 3dB
- Built-in priority relay
- Slim design
- Blends beautifully into walls
- Easy installation

► Applications

- Private houses
- Industrial buildings
- Public buildings
- Offices
- ...



The VC3022 are 100 Volt wall volume controllers with a maximum power handling of 20 Watt, for use in constant voltage public address audio systems.

The volume is adjustable using a rotatable dial in 11 steps of 3 dB.

It is equipped with a 24 Volts priority relay whereby it can be bypassed in priority situations. This can be useful for bypassing the volume controller to make sure an emergency message will always be heard at maximum volume.

Due to its slim and good looking design in a white finish, these volume controls will blend into all kinds of different environments or interiors.

The construction is made of sturdy ABS and therefore suitable for big projects in industrial buildings as well as standard home interiors.

The dimensions are 80 mm x 80 mm, and a maximum built-in depth of 35 mm is required.

The connections are made at the rear side with pluggable terminal block connectors.

► Specifications

SYSTEM SPECIFICATIONS	
Max. power handling	20 Watt
Max. operation voltage	100 Volt
Attenuation	11 x 3 dB
Priority relay	24 V - 25 mA
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	80 x 80 x 50 mm
Built-in depth	46 mm
Weight net	100 g
Construction	ABS
Colour	White
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	115 g - 0.0008Cbm
Optional accessories	WB3102/FS Flush mount wall box WB3102/SW Surface mount wall box
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our product	