

# 4 Port Giga + 1 Port Giga Powered Device PoE Switch

## PoES-0460G+1G(HPD)



- 4x1Gbps PoE Ports
- 1x1Gbps Ports (Powered Device)
- 55W (Avg:13.75W Max 30W per ch)
- Power Supplied from High Power PoE
- Distance: Up to 100 Meter
- Built-in Surge Protection
- Complies With IEEE802.3af/at

### Specifications

MODEL	PoES-0460G+1G(HPD)	
Interface	Downlink Ports	4 x 10/100/1000Mbps
	Uplink Ports	1 x 10/100/1000Mbps (Powered Device)
	SFP Ports	No
PoE	PoE Ports	4 (Downlink Ports)
	PoE Standard	IEEE802.3af/at PoE
	PoE Total Power	55W
	Average Power Per Channel	13.75W
	Maximum Power Per Channel	30W
Data Processing	Backbone Bandwidth	10Gbps
	Buffer Size	2Mb
	MAC Address Table	2K
	VLAN	No
Network Media	EIA/TIA-568	100Ω STP (Maximum 100m)
	10BASE-T	UTP Category 3, 4, 5 Cable (Maximum 100m)
	100BASE-TX	UTP Category 5, 5e Cable (Maximum 100m)
	1000BASE-T	UTP Category 5e, 6, 7 Cable (Maximum 100m)
Special	CCTV Mode	No
	Surge Protector	Built-In (±4KV)
	Wall Bracket	Optional
	Rack Bracket	No
Power	K-Slot (Anti Theft)	No
	PoE Status Monitor	No
Others	Power Supply	Powered by High Power PoE to PD Port or 54v/1.2A PSU (Not Supplied)
	Power Consumption	PoE On: 60W Max. / PoE Off: 3W Max.
	Fan	No
	Dimensions	160*93*28 mm
	Weight	1.32kg
	Operating Temperature	~0°C-40°C



PD Uplink Port (Powered Device)