

Fire Sounders

AS 260 Series



- Low current consumption from 3 mA onwards
- High sound output
- Multiple tones selection
- 12 - 24 V dc
- Automatic synchronisation
- Suitable for multiple stage evacuation
- Red and white colour body
- IP65 version
- Low profile version
- Version with xenon flash
- Red or clear lens for beacon

INSTALLER FRIENDLY

The AS 260 series feature a wide range of sounders tailored for every application, stand-alone or in combination with fire detectors. All types are compatible so that a synchronised phased start is guaranteed.

FLEXIBLE

Every sounder, except AS 266/267, is suitable for both 12 V dc and 24 V dc systems, no adjustment required. Aesthetically pleasing, the line features different sizes and red or white body colour.

EFFICIENT AND VERSATILE

Every sounder provides high sound output at a low current consumption, so reducing power standby requirements and system cost.

The AS 263/4 comes with a volume control as standard, allowing final audibility adjustments to be made during installation. The AS 264/7 are weather resistant to IP 65, utilising epoxy resin encapsulated electronics. The AS 266/7 are equipped with a xenon beacon providing an audio visual

warning signal, ideal for noisy environments or a dwellings with elderly people.

The low profile AS 268 has an extreme low current consumption and can be mounted directly under most industry standard detectors and be activated through the detectors remote output. Using a cover the sounder can be used stand alone. The AS 269 on the other hand comes with fixing positions for addressable PCBs.

The sounders can provide different tones (see tones table in manual), switch selectable during installation.

A second or third tone, model dependant, is available if extra wires are installed in the sounder circuit.

How to order

MODEL	DESCRIPTION
AS 263	Sounder, 26 tones - shallow base
AS 264	Sounder, 26 tones - deep base
AS 266	Combined sounder and beacon, 2 tones, red lens- shallow base
AS 267	Combined sounder and beacon, 2 tones, red lens- deep base
AS 268	Sounder, 4 tones, low profile - low current
AS 269	Sounder, 3 tones - low current

All listed sounders are red, add 'W' to the code for white body

Technical data

	AS 263/4	AS 266/7	AS 268	AS 269
Operation	Continuously rated			
Supply voltage dc	10-28	18-30	9-30	12-30
Current consumption as from ... mA onwards, (see tone table in manual)	7 mA	68 mA	3 mA	5 mA
Number of tones	26	2	4	3
Starting current	30 mA -2 msec	-	30 mA -10 msec	-
Automatic synchronisation	Phased start			
Line monitoring input	Polarised input			
Housing	ABS plastic			
Lens	Polycarbonate			
Ingress protection	IP65	IP65	IP42	IP42
Operating temperature	-40/+80 °C	-10/+55 °C	-25/+85 °C	-25/+70 °C
Dimension in mm (Ø x D)				
shallow base	93 x 75	93 x 92		
deep base	93 x 105	93 x 121		



The AS 260 series complies with the essential requirements of the EMC directive 89/336/EMC